

Material release

CompactFloor® EXPERT

Attention: Lay CompactFloor® EXPERT according to installation instructions. Leave adhesive to cure completely and keep surface free of dust. Process recommended products in accordance with manufacturer's instructions.

Parquet	8 mm mosaic block / herringbone	8 mm solid english bond straight / ladder pattern	10 mm solid parquet lamparquet	2- or 3-layer ready-made parquet short format less than 100 cm	2- or 3-layer ready-made parquet parquet plank / country style single plank	22 mm strip parquet and solid parquet	22 mm on-edge lamel parquet	Laminate Manufacturer release for full-surface bonding required
Adhesive	Bakit EK neu		Bakit ESP	Bakit EK neu			Bakit PU-P	
Primer	Okamul PU-V schnell							
Uncoupling fabric	not necessary	Okavlies	not necessary		Okaphone	Okavlies	not necessary	
If required	Okamul PU-V schnell							
Primer on leveling compound	Okamul PU-V schnell							
Leveling compound	Servoplan P200 Plus incl. Kiesel Armierungsfasern When using said leveling compound, a primer should be used under the leveling compound: Okatmos EG 20, 1:1 diluted with water							

Tiles / Natural stone	Ceramic tiles / Porcelain stoneware Tile size: max. 120 x 120 cm Minimum thickness: 9 mm Technical joint width: min. 3 mm		Natural stone Tile size: max. 120 x 120 cm Minimum thickness: 15 mm Technical joint width: min. 3 mm	
Joint mortar Test jointing recommended	Servoperl royal schnell			
Adhesive	Servoflex Trio SuperTec			
Primer	Okatmos UG 30, 1:1 diluted with water			
Uncoupling fabric	not necessary			
If required	Servoflex DMS 1K Plus SuperTec			
Sealing in damp rooms	Servoflex DMS 1K Plus SuperTec			
Primer on leveling compound	Okatmos UG 30, 1:1 diluted with water			
Leveling compound	Servoplan P200 Plus incl. Kiesel Armierungsfasern When using said leveling compound, a primer should be used under the leveling compound: Okatmos UG 30, 1:1 diluted with water			

Textile / Elastic floor coverings	Textile coverings	PVC / CV coverings design coverings	Needle punched flooring
Adhesive	Okatmos ET6	Okatmos star 100 / star 110 / star 120	Okatmos EN30
Primer	Okatmos EG 20		
If required	not necessary		
Primer on leveling compound	not necessary		
Leveling compound	Servoplan P200 Plus incl. Kiesel Armierungsfasern When using said leveling compound, a primer should be used under the leveling compound: Okatmos EG 20, 1:1 diluted with water		