

Material release

CompactFloor® EXPERT

Attention: Lay CompactFloor® EXPERT according to installation instructions. Leave adhesive to cure completely and keep surface free of dust. Process recommended products in accordance with manufacturer's instructions.

Tiles / Natural stones	Ceramic tiles / Porcelain stoneware Tile size: max. 80 x 80 cm Minimum thickness: 9 mm Technical joint width: min. 3 mm	Ceramic tiles / Porcelain stoneware Tile size: max. 120 x 120 cm Minimum thickness: 9 mm Technical joint width: min. 3 mm	Natural stone Tile size: max. 80 x 80 cm Minimum thickness: 15 mm Technical joint width: min. 3 mm
Joint mortar Test jointing recommended	Sopro DF 10® DesignFuge Flex or Sopro DF 20® DesignFuge Flex Breit		
Adhesive	S1-adhesive: Sopro's No.1 Flexkleber 400 or Sopro FKM® XL 444 S1-Instant adhesive: Sopro FKM® Silver 600	S2-adhesive: Sopro MG-Flex® MicroGum® Flexkleber S2 MG 669 or Sopro megaFlex S2 MEG 665 S2-Instant adhesive: Sopro MG-Flex® MicroGum® Flexkleber S2 MG 679 or Sopro megaFlex S2 turbo MEG 666	S1-Instant adhesive: Sopro FKM® Silver 600 For larger tile formats, consult the Sopro application technology department!
Primer	Sopro Primer GD 749 (1:1 diluted with water)		
If required	Sopro sealing slurry Flex 1-K DSF 523 or Sopro sealing slurry Flex 2-K DSF 423 or Sopro turbo sealing slurry 2-K TDS 823		
Primer on compensation	Sopro Primer GD 749 (1:1 diluted with water)		
Compensation	Sopro FS 15® plus 550 with an exact thickness of 5 mm		